

1841.80

Krypton XT LA-V

SAE 0W-30

Fully synthetic lubricant for latest generation gasoline and Diesel engines with exhaust gas post-treatment devices.

PAKELO KRYPTON XT LA-V SAE 0W-30 is a new generation fully synthetic lubricant formulated with selected high quality base stocks and exclusive additives that confer to the product high detergent, dispersant, anti-oxidative, anti-corrosion, anti-wear and antifoam properties.

The synthetic bases used reduce product volatility, oxidation and formation of carbon residues. This enables PAKELO KRYPTON XT LA-V SAE 0W-30 to provide extraordinary anti-oxidative properties and to avoid formation of deposits also under high working temperatures.

The low volatility of synthetic bases results into a very significant reduction of oil losses caused by evaporation.

The SAE Viscosity Grade 0W-30 guarantees the correct viscosity for the most severe climatic conditions: this means easy and safe start-ups at very low temperatures (also at -35°C) and reduction of wear risks to minimum.

Thanks to the special viscosity properties, the use PAKELO KRYPTON XT LA-V SAE 0W-30 can result into fuel savings and a prompt reply of the engine, making functioning soft and uniform.

PAKELO KRYPTON XT LA-V SAE 0W-30 improves protection of all modern engines. The use of exclusive additives with low content of Phosphorous, Sulphur and Sulphated Ash allows to extend working life of all post-treatment devices present in latest generation engines.

Low content of Ash helps to reduce PM content in DPF (Diesel Particulate Filter) used in modern Diesel engines.

Low content of Phosphorous and Sulphur avoids danger of "poisoning" in catalytic converters (CAT) of latest gasoline vehicles.

On the contrary the presence of these chemical elements affects life of post-treatment devices.

PAKELO KRYPTON XT LA-V SAE 0W-30 exceeds the main performance levels on the market. It is possible to extend oil drain intervals, according to Constructors' recommendations.

Oil drain intervals are usually specified by OEMs and/or on-board electronic devices of latest generation vehicles; their recommendations should be taken into consideration to guarantee engine reliability.

PAKELO KRYPTON XT LA-V SAE 0W-30 is perfectly compatible with all the lubricants that have the same application.

However, we recommend to avoid mixing it with other products for not undermining its exceptional properties.

1841.80

Krypton XT LA-V

SAE 0W-30

Application fields

PAKELO KRYPTON XT LA-V SAE 0W-30 is recommended for latest generation high performance gasoline and Diesel engines with exhaust gas post-treatment devices (CAT and DPF).

Ideal for gasoline engines (also direct injection) and direct injection, "common rail" or "pump-injector" turbocharged diesel engines.

Furthermore, thanks to synthetic base stocks used and to the low ash content, the product can also be used for natural gas and LPG engines.

Performance levels

ACEA C3, VW 504.00, VW 507.00, Porsche C30.

Approvals

Approved under **VW Standard 504 00** and **VW Standard 507 00**

Chemical-Physical Characteristics

Krypton XT LA-V	Method analysis	Unit measure	Value SAE 0W-30
Density at 15°C	ASTM D1298	kg/l	0,846
Kinematic Viscosity at 40°C	ASTM D445	cSt	60,6
Kinematic Viscosity at 100°C	ASTM D445	cSt	12,1
Viscosity Index	ASTM D2270	-	201
C.C.S. Viscosity at -35°C	ASTM D5293	cP	5850
HT-HS Viscosity at 150°C / 10 ⁶ s ⁻¹	ASTM D4683	cP	3,5
T.B.N. (Total Base Number)	ASTM D2896	mg(KOH)/g	7,8
Sulphated Ash	ASTM D874	% (w/w)	0,75
Flash Point (C.O.C.)	ASTM D92	°C	240
Pour Point	ASTM D97	°C	-51
Noack evaporability test	ASTM D5800	% (w/w)	10,0

The data just above refer to average values and must not be understood as guaranteed characteristics.

This Technical Data Sheet has been carefully checked to guarantee complete and precise information. However, we do not take any responsibility in case of damages caused by any mistakes or omissions. Due to continual product research and development, the information contained herein is subject to change without notification.