

Top Tec 4200 SAE 5W-30 New Generation



Description

Modern fully synthetic, low-SAPS motor oil for superior performance and long engine life. Designed for use in numerous Volkswagen and Audi vehicles and also suitable for use in a variety of BMW and Mercedes-Benz diesel vehicles as well as specific Porsche models, etc. Use with extended oil change intervals as per manufacturer.

Properties

- outstanding engine cleanliness
- ideal with turbochargers and catalytic converters
- optimum oil pressure under all operating conditions
- smooth engine running
- long engine service life
- optimum stability to aging
- high shear stability
- instant lubrication after cold start
- excellent wear resistance
- high lubrication reliability
- reduces pollutant emissions
- reduces fuel consumption

Specifications / Approvals

ACEA C3 • API SQ • BMW Longlife-04 • MB-Approval 229.31 • MB-Approval 229.51 • MB-Approval 229.52 • Opel OV 040 1547 - G30 / Opel OV 040 1547 - D30 • Porsche C30 • VW 504 00 • VW 507 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

ACEA C2 • BMW Longlife-01 (up to 2018)* • BMW Longlife-01 FE (up to 2018)* • Fiat 9.55535-S1 • Fiat 9.55535-S3 • GWM • HAVAL • VW 500 00 • VW 501 01 • VW 502 00 • VW 503 00 • VW 503 01 • VW 505 00 • VW 505 01 • VW 506 00 • VW 506 01 (With the exception of R5 and V10 TDI engines before 6/2006) • Wuling • *limited to BMW gasoline engines without particle filters in the EU including Norway, Switzerland, Great Britain and Liechtenstein

Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 59 °F	0,855 g/cm ³ DIN 51757
Viscosity at 104 °F	70,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	12,2 mm ² /s ASTM D 7042-04
Viscosity at -31 °F (MRV)	< 60000 mPas ASTM D4684

Technical data

Viscosity at -22 °F (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 302 °F	≥ 3,5 mPas ASTM D5481
Pour point	-43 °F DIN ISO 3016
Evaporation loss (Noack)	9,5 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	8,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Comment

⚠ WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	2004 CAEN-CAFR-USEN
5 l Canister plastic	2011 CAEN-CAFR-USEN

Top Tec 4200 SAE 5W-30 New Generation**Available pack sizes**

20 l Canister plastic	20125 CAEN-CAFR-USEN
60 l Black plate barrel	22086 CAEN-CAFR-USEN
205 l Black plate barrel	22087 CAEN-CAFR-USEN
1.000 l Container	3716 DE-EN
1.000 l Container	22155 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.